ELSEVIER

Contents lists available at ScienceDirect

### Journal of Power Sources

journal homepage: www.elsevier.com/locate/jpowsour



# Evolution of the electrocatalytic activity of carbon-supported amorphous platinum—ruthenium—nickel—phosphorous nanoparticles for methanol oxidation




Yanjiao Ma <sup>a</sup>, Hao Li <sup>b</sup>, Hui Wang <sup>a</sup>, Xuefeng Mao <sup>a</sup>, Vladimir Linkov <sup>c</sup>, Shan Ji <sup>c, 1</sup>, Oko Unathi Gcilitshana <sup>c</sup>, Rongfang Wang <sup>a, \*</sup>

- <sup>a</sup> College of Chemistry and Chemical Engineering, Northwest Normal University, Lanzhou 730070, China
- <sup>b</sup> Department of Chemical Engineering, Huizhou University, Huizhou, Guangdong 516007, China
- <sup>c</sup> South African Institute for Advanced Materials Chemistry, University of the Western Cape, Private Bag X17, Bellville, Cape Town 7535, South Africa

### HIGHLIGHTS

- Amorphous PtRuNiP/C catalyst with different disorder degree was prepared.
- Amorphous PtRuNiP-300/C catalyst showed high activity for methanol oxidation.
- The correlation between amorphous structure and their activity was established.

### G R A P H I C A L A B S T R A C T



### ARTICLE INFO

Article history: Received 25 February 2014 Received in revised form 4 June 2014 Accepted 17 June 2014 Available online 25 June 2014

Keywords:
Nanoparticles
Amorphous
Crystallinity
Electrocatalyst
Methanol oxidation

### ABSTRACT

Amorphous metallic nanoparticles hold much promise for use as electrocatalysts, as their surface is rich in low-coordination sites and defects which could act as the electrocatalyt's active sites. In this study, we describe new findings on amorphous platinum—ruthenium—nickel—phosphorous nanoparticles supported on carbon (PtRuNiP<sub>a</sub>/C) and the comparison between their catalytic activity and the degree of disorder. The nanoscale amorphous structure with different degrees of disorder are probed as a function of surface composition, particle size, and thermal treatment conditions using X-ray diffraction, X-ray photoelectron spectroscopy, transmission electron microscopy, selected area electron diffraction and electrochemical characterization. The results provide experimental evidence in support of nanoscale longrange disorder, medium-range disorder, and medium-range order evolution dependence on the catalysts synthesis temperature. More importantly, the results of the electrochemical performance investigation show that the amorphous structures with medium-range disorder have not only better catalytic activity, but also better durability for methanol oxidation compared to the long-range disorder and medium-range order structure. These results provide an opportunity for establishing the correlation between the nanoscale amorphous structure and their electrocatalytic activity for methanol oxidation reaction, which could play an important role in developing new high active catalysts for direct methanol fuel cells.

© 2014 Elsevier B.V. All rights reserved.

<sup>\*</sup> Corresponding author. Tel./fax: +86 931 7971533.

E-mail addresses: sji@uwc.ac.za (S. Ji), wrf38745779@126.com, wangrf@nwnu.edu.cn (R. Wang).

<sup>&</sup>lt;sup>1</sup> Tel./fax: +27 21 9599316.

### 1. Introduction

PtRu bimetallic electrocatalysts are considered as promising electrocatalysts for direct methanol fuel cells (DMFC) due to their high catalytic activity and CO tolerance [1]. In spite of making extensive efforts to optimize the structure and morphology of PtRu bimetallic catalysts to further improve their performance and, activity, their cost is still too high to meet the requirements for practical applications [2].

It is well demonstrated that the electrocatalytic characteristics such as activity, selectivity, and stability rely heavily on the surface atomic arrangement and configurations associated with terraces, steps, kinks and vacancies [3,4]. During the past decades, surface scientists have systematically studied the catalytic surface/structure correlations using metal single-crystal planes as model catalysts and found that the surfaces with an open structure (e.g. the high-index planes, denoted by a set of Miller indices (hkl) with at least one index being larger than unit) usually exhibit much high activity and stability [5,6]. High catalytic activity results from the high-index plane surfaces with high density of atomic steps and kinks, where low-coordinated atoms can easily interact with reactant molecules and serve as active sites for breaking chemical bonds [7]. Pt-based nanoparticles with high-index facets have been developed to meet the requirement of anode catalyst in DMFC [8]. Unfortunately, it is rather challenging to synthesize either high-index planes of bulk metals or Pt-based nanoparticles enclosed by high-index facets.

Amorphous alloys are a kind of metastable materials with longrange disordered but short-range ordered structure [9], which enable amorphous alloys to form a plenty of low-coordination sites (terraces, steps, corner atoms) and defects on the surface [10,11]. It is well-documented that low-coordination sites play important roles in catalysis. Ni and Co-based amorphous alloys have been employed as catalysts in many hydrogenation reactions [12,13]. Due to their superior corrosion resistance, amorphous alloys show very good stability during the catalysis process [10,11].

In the field of electrochemical catalysis, only a few studies have been reported on the amorphous electrocatalysts. For instance,  $N_iN_bPt$ -based amorphous electrocatalysts prepared by ball milling showed good electrocatalytic activity for small organic molecule oxidation [14]. PtRu-based amorphous electrocatalysts synthesized by chemical methods for small organic molecule oxidation were rarely explored. Therefore, it is an interesting work to develop amorphous structured PtRu-based catalysts with enhanced activity and stability.

Phosphorus, an inexpensive metalloid element, has several valence electrons. Some studies found that P element can enhance the electrocatalytic activity for small organic molecule oxidation [15–18]. Incorporating P into noble metal electrocatalysts has the following merits: (i) particle size reduction, which increases the amount of active sites [18,19]; (ii) reduction of particle agglomeration during the long-term operation of the fuel cell, leading to the good stability of electrocatalysts [18]; (iii) changes on the electronic states of the metal elements, resulting in the enhanced amount of Pt<sup>0</sup> formed in the electrocatalysts [20]. Moreover, it was proven that the small nanoparticle size of the crystalline PtRuNiP catalyst enhanced its catalytic activity for methanol oxidation [21].

Based on the above considerations, we synthesized PtRuNiP nanoparticles with an amorphous structure (denoted as PtRuNiP<sub>a</sub>/C) highly dispersed on the carbon surface, and investigated its catalytic activity towards methanol oxidation reactions. Moreover, the nanoparticles with various degrees of crystallinity, e.g. various degrees of disorder [22], were also prepared by heat-treatment at the appropriate temperature and their electrochemical performances were also systematically investigated. Comparison of the

results showed that the amorphous PtRuNiP electrocatalyst after heat-treatment at 300  $^{\circ}$ C exhibited the highest electrocatalytic activity and durability.

### 2. Experimental

## 2.1. Preparation of PtRuNiP/C catalysts with different degrees of crystallinity

Amorphous PtRuNiP/C catalyst was prepared by a NaBH4 reduction reaction in an aqueous solution. The detailed preparation process could be described as follows: 475 mg of NiCl $_2\cdot$ 6H $_2$ O, and 318 mg of NaH $_2$ PO $_2\cdot$ H $_2$ O were dissolved in aqueous solutions and stirred for 0.5 h. The pH of the system was adjusted to ~7.5 by the drop wise addition of a 6 mol L $^{-1}$  NaOH solution with vigorous stirring. And then 3.41 mL of 20 mg mL $^{-1}$  H $_2$ PtCl $_6$  and 1.76 mL of 20 mg mL $^{-1}$  RuCl $_3$  was rapidly added to the solution and with continuous stirring for another 0.5 h. Pretreated carbon black Vulcan $^{\$}$  XC72R (250 mg) was added to the mixture under stirring conditions. Afterward, 20 mL of 0.2 mol L $^{-1}$  NaBH $_4$  aqueous solution was added slowly to the mixture to react for 12 h. The product (PtRuNiP/C) was collected by filtration, washed with 6 mol L $^{-1}$  ammonia solution, then with deionized water several times and kept in ethanol solution.

The product was then thermally treated in a tube furnace under  $N_2$  atmosphere at 300, 500, and 700 °C for 2 h, respectively. The obtained products were then denoted as PtRuNiP-300/C, PtRuNiP-500/C, and PtRuNiP-700/C, respectively. For comparison, PtRu/C catalyst was prepared using the same procedure but the absence of the precursor of Ni and P.

### 2.2. Physical characterization

The catalysts were characterized by recording their X-ray diffraction (XRD) patterns on a Rigaku D/Max-2400 (Japan), using filtered Cu- $K_{\alpha}$  radiation ( $\lambda=0.15418$  nm), generated at 50 kV and 150 mA. Scans for  $2\theta$  values were recorded at  $4^{\circ}$  min<sup>-1</sup> between 10 and 90°. Transmission electron micrographs (TEM), high angle annular dark field scanning transmission electron microscopy (STEM) images and selected area electron diffraction (SAED) patterns of the catalysts were taken on a IEOL (IEM-2000 FX) microscope operating at 200 kV. Energy dispersive spectroscopy (EDS) in the STEM mode was employed for determining elemental composition of either individual particle or several particles. The crystallization behavior study was performed with a diffractometer scanning calorimetry (DSC) instrument system (Mettler Toledo) at a scan rate of 20 °C min<sup>-1</sup> up to 800 °C under N<sub>2</sub> atmosphere. X-ray photoelectron spectra (XPS) were acquired with a VG Escalab 210 spectrometer fitted with a Mg 300 W X-ray source.

### 2.3. Electrochemical measurements

The electrochemical measurements of the catalysts were performed using the electrochemical work station CHI 650D. A common three-electrode electrochemical cell was used for the measurements. The counter and reference electrodes were a platinum wire and an Ag/AgCl (3 mol  $L^{-1}$  KCl) electrode, respectively. The working electrode was a glassy carbon disk (5 mm in diameter). The thin-film electrode was prepared as follows: 5 mg of catalyst was dispersed ultrasonically in 1 mL Nafion/ethanol (0.25% Nafion) solution for 15 min. 8  $\mu L$  of the dispersion was transferred onto the glassy carbon disk using a pipette, and then dried in the air. The stable cyclic voltammograms (CVs) were recorded after 24 cycles. All potentials initially measured versus the Ag/AgCl electrode were




Fig. 1. Continuous heating DSC curves of PtRuNiPa sample at a heating rate of 10  $^{\circ}\text{C}$  min $^{-1}$ .




Fig. 2. The XRD patterns of the PtRuNiP/C catalysts.

converted to a RHE scale by adding 0.197 V (the potential of the Ag/AgCl reference measured against RHE).

### 3. Results and discussion

The optimization of the heat-treatment temperature of the amorphous PtRuNiP<sub>a</sub>/C to obtain the appropriate structure was the first goal of the study. Here, DSC measurement (see Fig. 1) was used to study the crystallization behavior of the amorphous PtRuNiP<sub>a</sub>/C. Considering the presence of carbon support which may make the data analysis difficult, un-supported sample was prepared for using in DSC measurement. One weak exothermic peak at around 700 °C can be observed in Fig. 1, which indicates that the phase transformation and crystallization of PtRuNiPa nanoparticles occurred at this temperature [12,23,24]. On the other hand, it was reported that the surface segregation of PtRu alloy also occurs at the temperature range from ca. 200–500 °C under different atmospheres [25–27]. Thus, the amorphous PtRuNiP<sub>a</sub>/C catalyst was heat treated at three temperatures i.e. 300, 500 and 700 °C, respectively, and the products were further studied. These products were denoted as PtRuNiP-300/C, PtRuNiP-500/C, and PtRuNiP-700/C, respectively.

The XRD patterns of all the prepared catalysts are presented in Fig. 2. All catalysts show a diffraction peak at about 24°, which corresponds to the (200) reflection of the hexagonal structure of Vulcan carbon. For the PtRuNiP<sub>a</sub>/C catalyst, no clear peak can be observed, suggesting that the structure of PtRuNiPa nanoparticles is amorphous and/or the crystallite size is very small [28-30]. For PtRuNiP-300/C catalyst, a weak broad peak within a wide  $2\theta$  range (36–49°) was observed, without any trace of sharp peaks related to the periodic lattice, which suggests that the PtRuNiP-300/C catalyst's structure is still amorphous. The relative strong intensity of a broad peak at ca. 43° was observed after the catalyst was heat-treated at 500 °C. This is a result of annihilation of point defects and dislocation [31,32] or partial crystallization [33]. After heat-treatment of the product at 700 °C, the XRD spectrum showed two new peaks at around 40 and 43°, which corresponds to the (110) plane of crystalline Pt alloy and (112) reflection of crystalline Ni<sub>3</sub>P phase (JCPDS card No. 34-0501), indicating that the phase-separated and the nanocrystalline structure is formed at around 700 °C [34,35].

Another technique used to give further information on structural changes is SAED patterns, which is shown as Fig. 3. A





Fig. 3. The SAED patterns of the PtRuNiP<sub>a</sub>/C (a), PtRuNiP-300/C (b), PtRuNiP-500/C (c) and PtRuNiP-700/C (d) catalysts.



**Fig. 4.** TEM images and the line-scan EDX profiles; the insets are the corresponding histogram of PtRuNiP particle size distribution in a-d and the STEM images in e-h, of the PtRuNiP<sub>a</sub>/C (a and e), PtRuNiP-300/C (b and f), PtRuNiP-500/C (c and g), and PtRuNiP-700/C (d and h) catalysts, respectively; The scale of red line in STEM images is consistent with that of horizontal axis of the line-scan EDX profiles. (For interpretation of the references to color in this figure legend, the reader is referred to the web version of this article.)

continuous hollow ring, which is a typical diffraction pattern of an amorphous material, can be observed in Fig. 3a, confirming the amorphous structure of PtRuNiP<sub>a</sub>/C [36]. For the SAED patterns of the products heat treated at 300 and 500 °C (Fig. 3b and c), no change was observed when compared to that of PtRuNiP<sub>a</sub>/C, indicating that the structure was still amorphous. However, for the 700 °C heat treated catalyst, some Laue spots were observed (Fig. 3d) indicating that the crystalline structure was formed [37]. The SAED results confirmed the results of the XRD and DSC.

Fig. 4a-d provides TEM images of the four catalysts and the corresponding rough histogram of the particle size distributions obtained by measuring about 100 randomly selected particles in the red box. Fig. 4e-h shows the line-scan EDS profiles and the corresponding STEM images (the insets). From Fig. 4a, it is evident that the PtRuNiP<sub>a</sub> nanoparticles are evenly distributed on the carbon surface, and the nanoparticle size distribution ranges from ~1.0-5.0 nm with the average particle size of ca. 1.8 nm. The composition of PtRuNiPa/C was analyzed by EDS and results are shown in Fig. S1 (Supporting information). The quantitative elemental analysis shows that the Pt:Ru:Ni:P atomic ratio is nearly 1.0:1.6:2.6:3.0, and the loading of PtRuNiP nanoparticles is ca. 19.8 wt%, which is obviously lower than the normal loading, implying that the metal precursors were partially reduced. The distribution profile of the elements is shown in Fig. 4e, in which the corresponding STEM images are presented. It can be seen that Pt manifests itself in two peaks, and the same is observed for all the other elements. The positions and widths of the peaks of all the elements match well with each other, showing that the four elements were evenly distributed in the PtRuNiP<sub>a</sub> nanoparticles.

In the TEM image of PtRuNiP-300/C, which is presented in Fig. 4b, the PtRuNiP-300 nanoparticles have a uniform and narrow size distribution with an average diameter of 3.0 nm. From this, it is evident that the heat-treatment at 300 °C induces agglomeration, which results in the increase in particle size. However, the distribution profile of the elements presented in Fig. 4f shows that the Ni, P, Ru and Pt elements are evenly distributed in the PtRuNiP-300 nanoparticles. Similarly, with PtRuNiP-500/C (Fig. 4c) and PtRuNiP-700/C (Fig. 4d and h), nanoparticles are also uniformly dispersed with an average particle size of 3.5 nm and 3.7 nm, respectively, with the distribution of the four elements also similar to that of the PtRuNiPa and PtRuNiP-300 nanoparticles (Fig. 4e).

As shown in Fig. 5, the range of the nanoparticle size broaden, and the average particle size increases as the temperature of heat-treatment increases from 300 to 700 °C. On the other hand, the uniform distribution of the Pt, Ru, Ni and P elements from




Fig. 5. The changes of the ECSA and average particle size of the four catalysts.

PtRuNiP<sub>a</sub>/C to PtRuNiP-700/C indicates that the alloy structure did not change with the heat treatment temperatures.

XPS analysis was carried out to determine the surface composition and the valence state of the catalysts. The XPS survey spectra of the all catalysts are shown in Supporting information, Fig. S2, in which O 1s, C 1s, P 2p, Ru 3p, Pt 4f, and Ni 2p signals were detected. By calculating the peak areas of elemental Pt, Ru, Ni, and P, the surface compositions of the four catalysts are provided in Table 1. The content of Ru, Ni and P follows a volcano curve trend compared to that of Pt, i.e. initially the content increases from PtRuNiP<sub>a</sub>/C to PtRuNiP-500/C and then decreases. By investigating the composition change of PtRu/C catalyst, Wang's group [25,38,39] found that the process of Ru surface segregation driven by atmospheric attraction competes with the Pt surface segregation driven by the surface energy. Thus, the surface segregations induced by the surface energy and the atmospheric attraction lead to the composition change on the surface of PtRuNiP nanoparticles.

The Pt 4f XPS of the four catalysts are shown in Fig. 6. The spectrum can be fitted into three pairs of doublets in all catalysts. The highest intense doublet is the Pt(0) peaks of metallic state, the middle one is the oxidation state Pt(II) in PtO and Pt(OH)<sub>2</sub>-like species, and the lowest one can be assigned to a higher oxidation state Pt(IV) [40,41]. The fitting results of the Pt  $4f_{7/2}$  component are listed in Table 1. It can be observed that Pt in all the catalysts is predominately presented in the zero valent metallic state, and the

**Table 1**Assignments, binding energies (BEs) and concentrations of Pt 4f species in various catalysts obtained from XPS results.

Catalyst	Pt:Ru:Ni:P <sup>a</sup>	Pt 4f <sub>7/2</sub>	BE <sup>b</sup>	Concentration <sup>c</sup>
PtRuNiP <sub>a</sub> /C	1.0:2.5:2.1:2.5	Pt(0)	71.9	0.25
		Pt(II)	72.7	0.45
		Pt(IV)	74.4	0.30
PtRuNiP-300/C	1.0:3.4:1.8:2.7	Pt(0)	71.9	0.16
		Pt(II)	72.8	0.55
		Pt(IV)	74.5	0.29
PtRuNiP-500/C	1.0:4.5:2.5:2.7	Pt(0)	71.9	0.27
		Pt(II)	72.5	0.46
		Pt(IV)	74.4	0.27
PtRuNiP-700/C	1.0:3.4:2.3:1.7	Pt(0)	71.7	0.28
		Pt(II)	72.3	0.51
		Pt(IV)	74.4	0.21

<sup>&</sup>lt;sup>a</sup> Atomic ratio.

<sup>&</sup>lt;sup>c</sup> Per species (in at %).




Fig. 6. The Pt 4f XPS spectra of the four catalysts.

<sup>&</sup>lt;sup>b</sup> Binding energy (in eV).

content of Pt(0) relative to the total quantity of Pt does not significantly change from PtRuNiP<sub>a</sub>/C to PtRuNiP-700/C.

However, it is obvious that the binding energies of Pt 4f show negative shifts from PtRuNiP<sub>a</sub>/C to PtRuNiP-700/C. The correlation of the shifts of the Pt 4f XPS binding energies with the electronic can provide important information about the relationship between their structural and electrochemical properties. It has been extensively studied by some groups [42–44] that the reduction of the metal particle size leads to the positive shift of binding energies. In the case of PtRuNiP/C catalysts, the negative shifts of binding energies from PtRuNiP-300/C to PtRuNiP-700/C are also the result of the particle sizes effect. However, the particle size effect cannot explain the positive shifts of Pt 4f binding energy of PtRuNiP-300/C and PtRuNiP<sub>a</sub>/C.

Based on the combined experimental and theoretical analysis of the shift, Richter et al. proposed that the origin of the initial or final state effects is connected to the lattice strain, and that the binding energy shift is related to the degree of hybridization being larger for shorter bond distances [45]. It should be noted that the above conclusions were obtained on the basis of the constant structure of the investigated particles. As previously discussed, the structure of PtRuNiP nanoparticles changed from nanoscale amorphous to partially crystalline phase when the heat treatment temperature was increased. During the process, annihilation of point defects and dislocation within the grains and grain boundary zones occurred along with rearrangement of atoms, which led to the change of the chemical bonding between Pt atoms with other atoms, and further resulted in the shift of binding energy. Besides, from PtRuNiP<sub>2</sub>/C to PtRuNiP-700/C, the shifts of binding energy do not vary monotonically with the particle size because the structure of the particles also changes. In particular, the highest binding energy shift of Pt 4f XPS in PtRuNiPa/C refers to the downshift of the center of the dband in respect to the Fermi level, which would lead to the decrease in the bond strength of adsorbents towards small molecule formed during the oxidation of methanol [46,47].

In the case of ruthenium, the Ru 3p signal can be deconvoluted into three distinguishable doublets with different intensities for PtRuNiP<sub>a</sub>/C and PtRuNiP-300/C, and two doublets for PtRuNiP-500/C and PtRuNiP-700/C (Fig. 7 and Table 2). The peak at 461.9–462.5 eV is attributed to metallic Ru (Ru(0)), while the two peaks at 463.9–464.1 and 466.2 eV in all catalysts are assigned to anhydrous RuO<sub>2</sub> and hydrous amorphous RuO<sub>2</sub>Hy [1,40]. The absence of RuO<sub>2</sub>·xH<sub>2</sub>O in PtRuNiP-500/C and PtRuNiP-700/C is as a result dehydration of RuO<sub>x</sub>Hy with heat-treatment at elevated temperature. As shown in Table 2, Ru in PtRuNiP<sub>a</sub>/C and PtRuNiP-300/C is predominately presented in the oxidation state, while




Fig. 7. The Ru 3p XPS spectra of the four catalysts.

**Table 2**Assignments, binding energies (BEs) and concentrations of Ru 3p species in various catalysts obtained from XPS results.

Catalyst	Ru 3p	BE <sup>a</sup>	Concentration <sup>b</sup>
PtRuNiP <sub>a</sub> /C	Ru	462.5	0.18
	$RuO_2$	464.1	0.64
	$RuO_xH_v$	466.2	0.18
PtRuNiP-300/C	Ru	462.2	0.09
	$RuO_2$	464.1	0.74
	$RuO_xH_v$	466.2	0.17
PtRuNiP-500/C	Ru	461.9	0.84
	$RuO_2$	463.9	0.16
	$RuO_xH_v$	_	_
PtRuNiP-700/C	Ru	462.1	0.84
	$RuO_2$	463.9	0.16
	$RuO_xH_y$	_	-

<sup>&</sup>lt;sup>a</sup> Binding energy (in eV).

most of Ru in PtRuNiP-500/C and PtRuNiP-700/C is in metallic state, which would influence the catalytic activity. In addition, the shifts of binding energy of Ru 3p can be clearly observed, and the trend is similar to that of Pt 4f binding energy. The result implies that the chemical bonding between Ru and the other atoms changes with the heat treatment temperature. The XPS spectra of Ni 2p and P 2p are presented in Figs. S3—S4 and Table S1—S2 in Supporting information.

A diagram shown in Fig. 8 illustrates the evolution of the surface and composition of PtRuNiP nanoparticles. The main structural feature of PtRuNiP<sub>a</sub> nanoparticles is a long-range disorder accompanied by a short-range order [32]. After the heat treatment, the amorphous phase is still retained, but annihilation of point defects and dislocation within the grains and grain boundary zones led to the medium-range disorder, i.e. the order range becomes longer [31], which is complemented by the rearrangement of atoms. Similar change of order range has been observed by Carlo and Alfredo in amorphous GeSe<sub>2</sub> [22]. When the heat treatment temperature increased, the order range became long, as shown in the structure of PtRuNiP-300/C and PtRuNiP-500/C. The phase transitioned from amorphous to crystalline phase occurs once the temperature was elevated to 700 °C where the exothermic peak appears. The medium-range order is formed in PtRuNiP-700/C.

Cyclic voltammograms (CVs) measured in a nitrogen-saturated  $0.5 \text{ mol } L^{-1} \text{ H}_2 SO_4 \text{ solutions are shown in Fig. 9. All catalysts}$ clearly exhibit the characteristic features of PtRu catalysts supported on carbon. It can be observed on the forward section of the first scan that there is a hydrogen desorption peaks in the low potential region (-0.03 to 0.297 V), and a peak at higher potential, between 0.797 V and 1.197 V corresponding to the oxidation of metal [48]. On the reverse scan, the peak at 0.737 to 0.567 V is the characteristic of metal oxide reduction and a hydrogen adsorption peak appears at low potential range [49]. The difference between these four catalysts is the capacitive current in the double-layer region. The capacitive current follows the order: PtRuNiP-300/  $C > PtRuNiP_a/C > PtRuNiP-500/C \approx PtRuNiP-700/C$ . The obtained capacitive current increases with the RuO<sub>2</sub> content. This capacitive current in the double-layer region is ascribed to the adsorption of oxygen-containing species (probably OH) on the Ru atoms, which plays an important role in the electrooxidation of methanol [50,51].

The electrochemical surface area (ECSA) is an important factor for the fuel cell reactions and the utilization ratio of electrocatalyst is closely connected with the ECSA. The ECSA values of the prepared catalysts were calculated according to the equation [51,52]:

$$ECSA = Q_{H}/(2.1\omega) \tag{1}$$

b Per species (in at %).




Fig. 8. Schematic illustration evolution of the structure of PtRuNiP nanoparticles.

where  $Q_{\rm H}$  (C m<sup>-2</sup>) is the average integrated charge in the hydrogen adsorption and desorption peak (-0.03 to 0.297 V) area of the CV curves after subtracting the contribution from the double-layer region,  $\omega$  is the Pt loading on the electrode, and 2.1 is the charge (C m<sup>-2</sup>) required to oxidize a monolayer of hydrogen on the precious metal surface, respectively. The values of ECSA are listed in Fig. 5, and it can be seen that the values of ECSA follow the order: PtRuNiP<sub>a</sub>/C  $\approx$  PtRuNiP-300/C > PtRuNiP-500/C  $\approx$  PtRuNiP-700/C. The PtRuNiP nanoparticles with amorphous structure have the largest ECSA value among all the prepared catalysts.

The electrocatalytic activities of the four prepared PtRuNiP/C catalysts towards methanol oxidation are shown in Fig. 10. For comparison, the activity of as-prepared PtRu/C was also displayed in the figure. The currents were normalized to the Pt + Ru loading and ECSA, corresponding to the mass activity and specific activity

respectively. Onset potential and the current of methanol oxidation at fixed potential were adopted to study of the catalytic activity for these four PtRuNiP/C catalysts, and the results are listed in Table 3. It can be observed that the onset potential of methanol oxidation on PtRu/C electrode is higher than those of the four PtRuNiP/C catalysts, suggesting that the presence of Ni and P can deduce the onset potential of methanol oxidation on PtRu particles. As shown in Table 3, the catalytic activities of these four catalysts follow the order: PtRuNiP-300/C > PtRuNiP<sub>a</sub>/C > PtRuNiP-500/C > PtRuNiP-700/C. The trend of the activity of four PtRuNiP/C catalysts is consistent with the values of ECSA. In addition, the catalytic activity of PtRu/C is in the middle in terms of the mass activity and specific activity, suggesting the appropriate dispersion of PtRuNiP nanoparticles can enhance the catalytic activity.





Fig. 9. CVs of the four PtRuNiP catalysts at  $N_2$ -saturated 0.5 mol  $L^{-1}$   $H_2SO_4$  solution with 50 mV  $s^{-1}$  of a scan rate.



**Fig. 10.** CVs of the all catalysts in 0.5 mol  $L^{-1}$  CH<sub>3</sub>OH + 0.5 mol  $L^{-1}$  H<sub>2</sub>SO<sub>4</sub> at 50 mV s<sup>-1</sup>; (a) and (b) are normalized by the Pt + Ru loading and ECSA<sub>H</sub>, respectively.


Fig. 11 shows the chronoamperometric curves of the catalysts measured in 0.5 mol L $^{-1}$  H $_2$ SO $_4$  and 0.5 mol L $^{-1}$  CH $_3$ OH at a constant potential of 0.797 V. For all catalysts, the potentiostatic current decreases rapidly in the initial period of time which can be due to the formation of CO $_{ads}$  and other intermediate species during the methanol oxidation reaction. The current density gradually decayed and a pseudo-steady state was achieved over time; this decay can be attributed to the adsorbed anion and intermediate present on the catalyst surface, restricting the methanol oxidation reaction [53]. The results demonstrate that the durability of these four catalysts follows the following order: PtRuNiP-300/C > PtRuNiP $_a$ CC > PtRuNiP $_a$ CC > PtRuNiP-500/C > PtRuNiP-700/C, and the durability of PtRu/C catalyst is poorer than those of four PtRuNiP/C catalysts in terms of the specific activity.

Based on the above electrochemical results, the electrocatalytic performance of the four catalysts shows a regular volcano trend. As

 Table 3

 Electrochemical characterizations of the five catalysts.

Catalyst	The onset potential of methanol oxidation (V vs. RHE)	The specific activity at 0.797 V (mA cm <sup>-2</sup> )	The mass activity at 0.797 V (mA mg <sup>-1</sup> <sub>PtRu</sub> )
PtRuNiP <sub>a</sub> /C	0.367	0.853	395
PtRuNiP-300/C	0.337	0.977	459
PtRuNiP-500/C	0.397	0.526	178
PtRuNiP-700/C	0.397	0.494	168
PtRu/C	0.451	0.874	418



**Fig. 11.** Chronoamperometry curves normalized by the Pt + Ru loading and ECSA<sub>H</sub>, of the all catalysts in 0.5 mol  $L^{-1}$  CH<sub>3</sub>OH + 0.5 mol  $L^{-1}$  H<sub>2</sub>SO<sub>4</sub> at fixed 0.797 V, respectively.

400

600

Time / s

800

1000

0.0

0

200

mentioned before, the electrocatalytic characteristics including activity and durability are strongly affected by the surface atomic arrangement and configuration associated with terraces, steps, kinks, and vacancies [3,4]. Therefore, these four catalysts can firstly be divided into two categories in terms of the component of Ru species obtained from XPS: i) PtRuNiP<sub>a</sub>/C and PtRuNiP-300/C, in which oxidized Ru is the major species; ii) PtRuNiP-500/C and PtRuNiP-700/C, where most of Ru species is metallic state. Moreover, the content of RuO<sub>x</sub>H<sub>v</sub> in PtRuNiP<sub>a</sub>/C and PtRuNiP-300/C is up to ca. 18% (see Table 2); while RuO<sub>x</sub>H<sub>v</sub> isn't found in PtRuNiP-500/C and PtRuNiP-700/C. It is generally considered that the existence of oxidized Ru species on PtRu catalysts will result in enhanced electrocatalytic performance; these oxidized Ru species act as active centers for the generation of Ru-OH species which are essential in lowering potentials for the oxidative removal of CO-like poisoning intermediates from the surfaces of PtRu catalysts [25,38,54,55]. The superior performance of the  $RuO_xH_v$ -rich PtRu catalysts is attributed to the uniqueness of RuO<sub>x</sub>H<sub>v</sub> as a mixed electron/proton conductor innately related with a Ru-OH speciation [56]. The beneficial effect of RuO<sub>x</sub>H<sub>y</sub> on methanol electrooxidation was thereafter frequently confirmed experimentally by several groups [57–59]. Based on these reports, it can be suggested that the existence of RuO<sub>x</sub>H<sub>v</sub> in PtRuNiP<sub>a</sub>/C and PtRuNiP-300/C is one of the factors which lead to the high catalytic activity. Moreover, the ECSA of PtRuNiP<sub>a</sub>/C and PtRuNiP-300/C are larger than those of PtRuNiP-500/C and PtRuNiP-700/C, which can also improve the catalytic activity. In addition, based on XPS data, the bond strength of adsorbents towards small molecule for PtRuNiP $_a$ /C and PtRuNiP-300/C is lower than PtRuNiP-500/C and PtRuNiP-700/C, which could result in high catalytic activity due to rapid removal of intermediates to recover the active sites [60].

On the other hand, for PtRuNiP<sub>a</sub>/C and PtRuNiP-300/C, the surface composition and ECSA values are almost same, and the average particle size of PtRuNiP-300 nanoparticles is larger than that of PtRuNiP<sub>a</sub>, but PtRuNiP-300/C exhibits higher catalytic activity than PtRuNiP<sub>a</sub>/C. Why is this so? Because, as shown in Fig. 8, heattreatment at 300 °C, annihilation of point defects and dislocation within the grains and grain boundary lead to the long-range disorder in PtRuNiP<sub>a</sub> nanoparticles, along with the rearrangement of atoms. The changed range of disorder alters the electron state around atoms, which presents itself as the slightly positive shift of Pt 4f binding energy from PtRuNiP<sub>a</sub>/C to PtRuNiP-300/C, implying the bond strength of adsorbates towards small molecules on PtRuNiP-300/C decreases compared to PtRuNiP<sub>a</sub>/C, resulting in increased catalytic activity.

However, when the heat treatment temperature continually increase, the Pt 4f binding energy shifts to lower value, indicating that the bond strength of adsorbents towards small molecules increases which leads to low catalytic activity. Thus, the catalytic activity of PtRuNiP-500/C is higher than that of PtRuNiP-700/C. From the above results it can be concluded that in amorphous PtRuNiP nanoparticles, there is an optimum range of disorder which can be controlled by thermal treatment in order to achieve the highest catalytic activity.

### 4. Conclusions

In this study, the characterization results obtained using DSC, XRD, SAED, TEM, line-scan EDS and XPS have provided important information to explain the changes of long-range disorder, medium-range disorder and medium-range order as a function of the thermal treatment temperature. With the heat treatment temperature increase, the structure of PtRuNiPa nanoparticles changed from long-range disorder to medium-range disorder, and the PtRuNiP nanoparticles became partial crystalline at 700 °C. CVs and chronoamperometry were carried out to study electrocatalytic performance. It was found that the catalytic activities as a function of the heat-treatment showed a volcanic curve trend and reached the peak when the heat treatment temperature was 300 °C which was caused by two factors, namely, the change of surface composition and the electronic effect which resulted from the changed range of disorder. The results are expected to pave the way for developing another strategy for developing amorphous multimetallic nanoscale catalysts with high activity and durability for electrocatalytic reactions.

### Acknowledgments

The authors acknowledge the National Natural Science Foundation of China (21363022, 21163018, and 51362027) for providing funding for this research.

### Appendix A. Supplementary data

Supplementary data related to this article can be found at http://dx.doi.org/10.1016/j.jpowsour.2014.06.091.

### References

[1] L. Ma, C. Liu, J. Liao, T. Lu, W. Xing, J. Zhang, Electrochim. Acta 54 (2009) 7274–7279.

- [2] G. Wu, R. Swaidan, D. Li, N. Li, Electrochim. Acta 53 (2008) 7622-7629.
- [3] Z. Quan, Y. Wang, J. Fang, Acc. Chem. Res. 46 (2013) 191.
- [4] W.P. Zhou, A. Lewera, P.S. Bagus, A. Wieckowski, J. Phys. Chem. C 111 (2007) 13490—13496.
- [5] N. Tian, Z.-Y. Zhou, S.G. Sun, J. Phys. Chem. C 112 (2008) 19801–19817.
- [6] W. Chrzanowski, A. Wieckowski, Langmuir 13 (1997) 5974–5978.
- [7] S. Jones, K. Tedsree, M. Sawangphruk, J.S. Foord, J. Fisher, D. Thompsett, S.C.E. Tsang, ChemCatChem 2 (2010) 1089–1095.
- [8] N. Tian, Z.-Y. Zhou, S.-G. Sun, Y. Ding, Z.L. Wang, Science 316 (2007) 732–735.
- [9] W.Y. Wong, W.R.W. Daud, A.B. Mohamad, A.A.H. Kadhum, K.S. Loh, E.H. Majlan, Int. J. Hydrogen Energy 38 (2013) 9370–9386.
- [10] K. Asami, A. Kawashima, A. Hashimoto, Mater. Sci. Eng. 99 (1998) 475.
- [11] K. Wang, H. Wang, R. Wang, J. Key, V. Linkov, S. Ji, S. Afr. J. Chem. 66 (2013) 86–91.
- [12] T.F. Hung, M.H. Tu, C.W. Tsai, C.J. Chen, R.S. Liu, W.R. Liu, M.Y. Lo, Int. J. Hydrogen Energy 38 (2013) 3956–3962.
- [13] M. Muraoka, H. Tomonaga, M. Nagai, Fuel 97 (2012) 211–218.
- [14] J. Barranco, A.R. Pierna, J. Non-Cryst. Solids 353 (2007) 851-854.
- [15] G. Yang, Y. Chen, Y. Zhou, Y. Tang, T. Lu, Electrochem. Commun. 12 (2010) 492–495
- [16] X. Xue, J. Ge, T. Tian, C. Liu, W. Xing, T. Lu, J. Power Sources 172 (2007)  $560{-}569. \\$
- [17] X. Xue, J. Ge, C. Liu, W. Xing, T. Lu, J. Electrochem. Commun. 8 (2006) 1280–1286.
- [18] M.L. Lin, M.Y. Lo, C.Y. Mou, Catal. Today 160 (2011) 109-115.
- [19] H. Daimon, Y. Kurobe, Catal. Today 111 (2006) 182–187.
- [20] L.X. Ding, A.L. Wang, G.R. Li, Z.Q. Liu, W.X. Zhao, C.Y. Su, Y.X. Tong, J. Am. Chem. Soc. 134 (2012) 5730–5733.
- [21] S.H. Lee, D.J. Kim, Y.S. Yoon, Jpn. J. Appl. Phys. 52 (2013) 035001.
- [22] C. Massobrio, A. Pasquarello, Phys. Rev. B 77 (2008) 144207—144216.
- [23] J.N. Balaraju, Kalavati, N.T. Manikandanath, V.K. William Grips, Surf. Coat. Technol. 206 (2012) 2682–2689.
- [24] H. Huang, H. Chen, D. Sun, X. Wang, J. Power Sources 204 (2012) 46-52.
- [25] Y.C. Wei, C.W. Liu, W.J. Chang, K.W. Wang, J. Alloys Compd. 509 (2011) 535–541.
- [26] S.Y. Huang, S.M. Chang, C.L. Lin, C.H. Chen, C.T. Yeh, J. Phys. Chem. B 110 (2006) 23300—23305.
- [27] W. Wang, Y. Li, H. Wang, Reac. Kinet. Mech. Cat. 108 (2013) 433-441.
- [28] H. Wang, X. Zhang, R. Wang, S. Ji, W. Wang, Q. Wang, Z. Lei, J. Power Sources 196 (2011) 8000–8003.
- [29] H. Wang, S. Ji, W. Wang, R. Wang, S. Afr. J. Chem. 66 (2013) 17-20.
- [30] H. Li, J. Liao, X. Zhang, W. Liao, L. Wen, J. Yang, H. Wang, R. Wang, J. Power Sources 239 (2013) 277–283.
- [31] H.W. Sheng, W.K. Luo, F.M. Alamgir, J.M. Bai, E. Ma, Nature 439 (2006) 419–425.
- [32] T.C. Hufnagel, Nat. Mater. 3 (2004) 666–667.
- [33] H. Peng, Z. Mo, S. Liao, H. Liang, L. Yang, F. Luo, H. Song, Y. Zhong, B. Zhang, Sci. Rep. 3 (2013) 1765.
- [34] X.L. Wang, H. Wang, Z.Q. Lei, Z. Zhang, R.F. Wang, Chin. J. Catal. 32 (2011) 1519–1524.
- [35] B.N. Wanjala, J. Luo, R. Loukrakpam, B. Fang, D. Mott, P.N. Njoki, M. Engelhard, H.R. Naslund, J.K. Wu, L. Wang, O. Malis, C.J. Zhong, Chem. Mater. 22 (2010) 4282–4294.
- [36] L. Xu, G. Zhang, J. Chen, Y. Zhou, G.e. Yuan, F. Yang, J. Power Sources 240 (2013) 101–108.
- [37] L. Wei, Y.-J. Fan, J.-H. Ma, L.-H. Tao, R.-X. Wang, J.-P. Zhong, H. Wang, J. Power Sources 238 (2013) 157–164.
- [38] S.Y. Huang, C.M. Chang, K.W. Wang, C.T. Yeh, ChemPhysChem 8 (2007) 1774–1777.
- [39] Y.C. Wei, C.W. Liu, K.W. Wang, ChemPhysChem 10 (2009) 1230–1237.
- [40] J.L. Gómez de la Fuente, M.V. Martínez-Huerta, S. Rojas, P. Hernández-Fernández, P. Terreros, J.L.G. Fierro, M.A. Peña, Appl. Catal. B 88 (2009) 505–514
- [41] Y. Liang, J. Li, Q.-C. Xu, R.-Z. Hu, J.-D. Lin, D.-W. Liao, J. Alloys Compd. 465 (2008) 296–304.
- [42] M. Cini, M. De Crescenzi, F. Patella, N. Motta, M. Sastry, F. Rochet, R. Pasquali, A. Balzarotti, C. Verdozzi, Phys. Rev. B 41 (1990) 5685–5695.
- [43] M.G. Mason, Phys. Rev. B 27 (1983) 748-762.
- [44] G.K. Wertheim, S.B. DiCenzo, D.N.E. Buchanan, Phys. Rev. B 33 (1986) 5384–5390.
- [45] B. Richter, H. Kuhlenbeck, H.J. Freund, P. Bagus, Phys. Rev. Lett. 93 (2004) 026805.
- [46] W.P. Zhou, A. Lewera, R. Larsen, R.I. Masel, P.S. Bagus, A. Wieckowski, J. Phys. Chem. B 110 (2006) 13393–13398.
- [47] X. Zhang, H. Wang, J. Key, V. Linkov, S. Ji, X. Wang, Z. Lei, R. Wang, J. Electrochem. Soc. 159 (2012) B270–B276.
- [48] J. Prabhuram, T.S. Zhao, Z.K. Tang, R. Chen, Z.X. Liang, J. Phys. Chem. B 110 (2006) 5245–5252.
- [49] P. Hernandez-Fernandez, R. Nuno, E. Fatas, J.L.G. Fierro, P. Ocon, Int. J. Hydrogen Energy 36 (2011) 8267–8278.
- [50] L.P.R. Profeti, D. Profeti, P. Olivi, Int. J. Hydrogen Energy 34 (2009) 2747–2757.
- [51] H.A. Gasteiger, N. Markovic, P.N. Ross, E.J. Cairns, J. Phys. Chem. 97 (1993) 12020–12029.

- [52] C. Zhou, H. Wang, F. Peng, J. Liang, H. Yu, J. Yang, Langmuir 25 (2009)
- [53] H. Li, D.L. Kang, H. Wang, R.F. Wang, Int. J. Electrochem. Sci. 6 (2011) 1058-1065.
- [54] H.B. Suffredini, V. Tricoli, N. Vatistas, L.A. Avaca, J. Power Sources 158 (2006) 124-128.
- [55] S.Y. Huang, C.T. Yeh, J. Power Sources 195 (2010) 2638–2643.
  [56] D.R. Rolison, P.L. Hagans, K.E. Swider, J.W. Long, Langmuir 15 (1999) 774–779.
- [57] S. Zhu, S. Wang, Y. Gao, L. Jiang, H. Sun, G. Sun, Int. J. Hydrogen Energy 35 (2010) 11254–11260.
- [58] J.H. Ma, Y.Y. Feng, J. Yu, D. Zhao, A.-J. Wang, B.Q. Xu, J. Catal. 275 (2010) 34–44.
   [59] B. Shyam, T.M. Arruda, S. Mukerjee, D.E. Ramaker, J. Phys. Chem. C 113 (2009)
- 19713-19721.
- [60] X. Mao, L. Yang, J. Yang, J. Key, S. Ji, H. Wang, R. Wang, J. Electrochem. Soc. 160 (2013) H219-H223.